

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number  
**WO 2005/082214 A1**

(51) International Patent Classification<sup>7</sup>: **A47J 37/10**

[US/US]; 8064 Clifton Court Circle NW, Massillon, OH 44646 (US).

(21) International Application Number:

PCT/US2005/005812

(74) Agent: **MOXON, George, W., II**; Roetzel & Andress, 222 South Main Street, Akron, OH 44308 (US).

(22) International Filing Date: 25 February 2005 (25.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/547,706 25 February 2004 (25.02.2004) US

(71) Applicant (for all designated States except US): **AND-HOW INNOVATIONS, LLC**. [US/US]; 59 Valley Road Blvd., Hinkley, OH 44233 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): **LOEWENTHAL, Howard, Lee** [US/US]; 59 Valley Brook Blvd., Hinkley, OH 44233 (US). **SPRIEGEL, Andrew, Raymond**

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: LEAK RESISTANT SIPHONING DEVICE FOR USE IN FLUID TRANSFER



(57) Abstract: An improved, leak resistant, siphoning device that includes an elongated hollow body member (14), a means for filling and emptying the hollow body member, such as an elastomeric resilient suction bulb (10) and a valve (17,18) placed between the hollow member and the filling/emptying means. The suction bulb (10) defines a chamber therein, so that when it is squeezed and released it will create suction to direct fluid up through the first open head end into the elongated hollow body member using pressure differential. Squeezing the suction bulb (10) can release the liquid and partial solids held within the elongated hollow body member (14) out of the first open head end. The suction bulb (10) also has an optional opening (170) for venting heated air from the bulb, and a means to selectively close the opening for creating vacuum or pressure required to draw or expel liquid from the tube.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,  
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*